

Fiber Distribution Chassis

ST/SC/LC/FC Enclosed Feedthrough Chassis



- Feedthrough Fiber Couplers
- ST/SC/LC/FC Versions
- Fully Enclosed Chassis
- Aluminum or Stainless Steel Panel
- 6, 12, or 24 Positions
- 1RU or 2RU Height
- Rear Ports for Cable Grips

Part Number: **FB(height)(faceplate type) - (connector type)(fiber type) - (number of positions)**

Description: Feedthrough Fiber Distribution Chassis

Options: **Height:** 1RU or 2RU

Faceplate Type: (blank) = Aluminum, SS = Stainless Steel

Connector Type: ST, SC, LC, FC

Fiber Type: S=Single-mode, MM1 = 62.5u Multi-mode (beige), MM2 = 50u Multi-mode (black), MM3 = 50u 10G Multi-Mode (aqua)

Number of Positions: 6, 12, 24

Specifications

Connectors	Chassis Dimensions	Material and Finish	Rear Ports
ST Feedthrough with Dustcap and Lanyard SC Feedthrough with Dustcovers LC Feedthrough with Dustcovers FC Feedthrough	1RU VERSIONS: 19"W x 1.75"H x 5.75"D 2RU VERSIONS: 19"W x 3.5"H x 5.75"D	Anodized Aluminum or Stainless Steel Front Panel, Anodized Aluminum Back Chassis	(2) 1.120" Punched Holes (2) .870" Punched Holes