

## Neutrik® opticalCon® QUAD Fiber Assemblies

Four-Channel Tactical for Commercial AV Applications



- Heavy Duty Tactical Fiber Cable
- Rugged Connector Body
- Self-Actuating Protective Shutters
- SM or MM OM3 Fiber
- Four Strand Fiber
- LC 1.25mm Contacts
- Protective Overbody Boots
- Integrated Dust Caps with Lanyards

Part Number: **X - NOC4(fiber type) - (length)**  
 Description: Neutrik opticalCon QUAD Tactical Fiber Assembly  
 Options: **Fiber Type:** S=Single-mode, M=Multi-mode 50u OM3  
**Length:** Any up to 5000'

### Components

Cable Type	OC-0003358 (MM) or OC-0003166 (SM) SM or MM 50u OM-3 Glass Fiber 4 Strands UV Cured Acrylate Hard Elastomeric Tight Buffer Aramid Yarn	Overall Jacket: Black Polyurethane
Connector Type	Neutrik opticalCon QUAD Advanced Overbody Rubber Boot with Integrated Dust Caps and Lanyards	Connector Finish: Dark Grey

### Performance Characteristics

Optical Attenuation and Return Loss	Minimum Bend Radius	Operating Temperature
>0.5db + 0.70dB/km (SM @ 1310nm/1550nm) >0.5dB + 3.00dB/km (MM 50u OM-3 @ 850nm) >0.5dB + 1.00dB/km (MM 50u OM-3 @ 1310nm)  >45dB SRL (-55dB Typical) SM	1.7"	-55°C to +85°C

Neutrik and opticalCon are registered trademarks of Neutrik AG

#A7401